



The Vogue decorative film is composed of a systematic repeating pattern that customises your windows and glass surfaces. The use of geometric shapes on your glazing or glass partitions is an excellent way to brighten up any space. In this case, the design imitates fluted glass.

### Certifications



**Warranty SOLAR SCREEN®**  
See the 'New guarantees for outdoor products' notice



**Fire-Resistance Rating**



**Storage From -5°C To +40°C**  
3 years



**Reach Rohs Compliant**  
Respected



**EN 13541 Standard**  
Not respected



**European Standard EN 12600**  
Not respected



**EN 356 Standard**  
Not respected



**Widths Available**  
152cm

### Construction

1. High optical quality polyester with engraved pattern
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

### Maintenance Instructions

Soapy water solution (ref. Film On 600-F0355), do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

### Technical Datasheet

Ultraviolet Transmission	15%
Visible Light Transmission	65%
Reflection Of External Visible Light	NC
Reflection Of Internal Visible Light	NC
Total Solar Energy Rejected	NC
Total Solar Energy Rejected 2*	NC
Solar Ratio :	
Solar Energy Reflection	NC
Solar Energy Absorption	NC
Solar Energy Transmission	NC
Reduction In Solar Glare	NC
G-Value	NC
U-Value	NC
Heat Loss Reduction (Winter)	NC
Rejected Infrared (760-2500 Nm)	NC
Shading Coefficient	NC
Installation Type : Indoor	
Roll Length	30.5 m m
Film Composition	PET

### Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Caution ! Not Recommended

\*Advice based on glass surface up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.

Thickness

90μ μ

Colour From The Outside :

DEPOLI

SOLAR SCREEN® EUROPEAN SALES CENTER 18 Rue du Commerce L-3895 FOETZ TEL : +33 1 64 61 64 20 [WWW.SOLARSCREEN.EU](http://WWW.SOLARSCREEN.EU)